



















within a recessed contour cavity on the surface of the UAV that allow to lock the rear side of the triangle (822) having an undercut shaped edge, locking angle, (825 in FIG. 8b) relative to the lower surface of the triangle (824) that may work as a hinge in the moment of the arm (812) when the front cable (820) is pulling back and released the other edges (802 and 804) which may be shaped in draft angles (826 in FIG. 8c) relative to the lower surface of the triangle (824). This structure enables the parachute release mechanism to disconnect from the recessed cavity with no stress and in any direction. By this action the parachute is not connected to the UAV and cannot cause any damages. The parachute (not shown) is connected to the device by three lines (cables) (816), (818) and (820) which are connected to one cable (810) in one point (814).

FIG. 9 describes, according to exemplary embodiments, a parachute release device (900). The parachute release device may include, according to some embodiments, a servo actuator (902), a link (504) connected to a release arm (906) with the bearing on it (908), a connecting element shaped as a triangle (910) with the locking arm (912). The parachute (not shown) is connected to the device by three lines (cables). The servo (902) and the locking mechanism (components 906 and 908) may be connected to the fuselage by element (926) using screws (930).

The devices and methods referred to herein may also function, operate, be used, structured and/or designed according to any part of the disclosure of U.S. application Ser. No. 60/719,583, incorporated herein by reference.

\* \* \* \* \*

