

[USPTO PATENT FULL-TEXT AND IMAGE DATABASE](#)[Home](#)[Quick](#)[Advanced](#)[Pat Num](#)[Help](#)[Next List](#)[Bottom](#)[View Cart](#)

Searching US Patent Collection...

**Results of Search in US Patent Collection db for:****AN/Swagelok AND AC/Solon: 171 patents.****Hits 1 through 50 out of 171**[Next 50 Hits](#)[Jump To](#) [Refine Search](#) AN/Swagelok AND AC/Solon

<b>PAT. NO.</b>	<b>Title</b>
1	<a href="#">D884,130</a> <a href="#">Back ferrule</a>
2	<a href="#">10,648,749</a> <a href="#">Fluid system components with thermal conditioning passages</a>
3	<a href="#">10,648,598</a> <a href="#">Ferrule for a conduit fitting</a>
4	<a href="#">10,648,596</a> <a href="#">Method of assembling a conduit fitting</a>
5	<a href="#">10,648,595</a> <a href="#">Component retaining structure for conduit fitting</a>
6	<a href="#">D882,434</a> <a href="#">Laminar flow element</a>
7	<a href="#">10,619,780</a> <a href="#">Single action push to connect conduit fitting</a>
8	<a href="#">10,619,770</a> <a href="#">Ferrule assembly for conduit fitting</a>
9	<a href="#">10,619,744</a> <a href="#">Valve with self-aligning stem tip</a>
10	<a href="#">D880,284</a> <a href="#">Face seal fitting nut</a>
11	<a href="#">10,604,832</a> <a href="#">Enhanced activation of self-passivating metals</a>
12	<a href="#">10,591,092</a> <a href="#">Hybrid hose assembly</a>
13	<a href="#">10,584,820</a> <a href="#">Push to connect conduit fitting with ferrule</a>
14	<a href="#">10,584,814</a> <a href="#">Conduit fitting with stroke resisting features</a>
15	<a href="#">10,578,503</a> <a href="#">System and methods for strain detection in a coupling</a>
16	<a href="#">10,458,582</a> <a href="#">Single action push to connect conduit fitting with colletting</a>
17	<a href="#">10,415,730</a> <a href="#">Conduit gripping device having retaining structure for conduit fitting</a>
18	<a href="#">10,415,727</a> <a href="#">Conduit fitting with attached torque collar</a>
19	<a href="#">10,359,134</a> <a href="#">Component retaining structure for conduit fitting</a>
20	<a href="#">10,344,898</a> <a href="#">Pull-up by torque fitting with female threaded nut and integral dynamic wedge</a>
21	<a href="#">10,344,875</a> <a href="#">Valve and valve with seat insertion tool and extraction tool</a>
22	<a href="#">10,316,998</a> <a href="#">Conduit fitting subassembly and retaining tool</a>
23	<a href="#">10,316,997</a> <a href="#">Fitting assembly evaluating apparatus and methods</a>
24	<a href="#">10,315,939</a> <a href="#">Diaphragm valve with diaphragm seat carrier</a>
25	<a href="#">10,295,093</a> <a href="#">Conduit connection with sensor on a threaded body</a>
26	<a href="#">10,247,336</a> <a href="#">Conduit gripping device having retaining structure for conduit fitting</a>
27	<a href="#">10,246,766</a> <a href="#">Concurrent flow of activating gas in low temperature carburization</a>

- 28 [10,214,805](#)  [Enhanced activation of self-passivating metals](#)
- 29 [10,156,006](#)  [Low temperature carburization under soft vacuum](#)
- 30 [10,100,955](#)  [Advanced geomerty ferrule](#)
- 31 [10,047,887](#)  [Conduit gripping device having retaining structure for conduit fitting](#)
- 32 [10,024,468](#)  [Conduit fitting with components adapted for facilitating assembly.](#)
- 33 [9,958,100](#)  [Push to connect conduit fitting with ferrule](#)
- 34 [9,958,097](#)  [Conduit fitting with flexible torque collar](#)
- 35 [9,903,518](#)  [Single action push to connect conduit fitting](#)
- 36 [9,863,542](#)  [Diaphragm valve with welded diaphragm seat carrier](#)
- 37 [9,851,032](#)  [Conduit fitting with torque collar](#)
- 38 [9,835,256](#)  [Self-aligning valve seal](#)
- 39 [9,810,328](#)  [Valve and valve with seat insertion tool and extraction tool](#)
- 40 [9,778,149](#)  [Fluid sample system and method](#)
- 41 [9,777,858](#)  [Coated seals](#)
- 42 [9,617,632](#)  [Concurrent flow of activating gas in low temperature carburization](#)
- 43 [9,611,961](#)  [Pull-up by torque fitting with female threaded nut and integral dynamic wedge](#)
- 44 [9,562,635](#)  [Conduit fitting with pull-up indication](#)
- 45 [9,556,981](#)  [Fitting assembly evaluating apparatus](#)
- 46 [9,556,979](#)  [Fitting assembly evaluating apparatus](#)
- 47 [9,441,769](#)  [Method of assembling conduit fitting with attached torque collar](#)
- 48 [9,400,070](#)  [Conduit fitting with sensor on a threaded nut](#)
- 49 [9,383,048](#)  [Ferrule with internal recess and cylindrical wall](#)
- 50 [9,297,481](#)  [Conduit fitting with torque collar](#)
- 

