

USPTO PATENT FULL-TEXT AND IMAGE DATABASE[Home](#)[Quick](#)[Advanced](#)[Pat Num](#)[Help](#)[Bottom](#)[View Cart](#)

Searching US Patent Collection...

Results of Search in US Patent Collection db for:**AN/"Wisk Aero" AND AC/"Mountain View": 25 patents.****Hits 1 through 25 out of 25**

Jump To

Refine Search

AN/"Wisk Aero" AND AC/"Mountain View"

PAT. NO.**Title**

- 1 [10,903,535](#)  [Aircraft hybrid cooling system](#)
- 2 [10,873,111](#)  [Battery with compression and prevention of thermal runaway propagation features](#)
- 3 [10,868,430](#)  [Multi-battery charging station which selectively connects battery sub-modules to a common power bus for charging](#)
- 4 [10,859,401](#)  [Fault tolerant servo sensor with linear hall sensors and discrete hall sensors](#)
- 5 [10,761,557](#)  [Magnetic spring inceptor](#)
- 6 [10,756,398](#)  [Capacitance reducing battery submodule with thermal runaway propagation prevention and containment features](#)
- 7 [10,749,211](#)  [Generation of wrinkle-free silicon monoxide electrodes using separate preformation and formation](#)
- 8 [10,745,099](#)  [Conductor in composite](#)
- 9 [10,744,890](#)  [Electric vehicle power distribution system](#)
- 10 [10,741,805](#)  [Battery submodule assembly fixture with multiple actuators](#)
- 11 [10,727,551](#)  [Battery with liquid temperature controlling system](#)
- 12 [10,673,252](#)  [Multi-battery charging station which selectively connects battery sub-modules to a common power bus for charging](#)
- 13 [10,648,953](#)  [Ultrasonic weld quality testing using audio](#)
- 14 [10,647,408](#)  [Composite structure with integrated hinge](#)
- 15 [10,640,197](#)  [Composite airfoil with rolled fiberglass reinforced leading edge](#)
- 16 [10,637,333](#)  [Non-invasive rubbing detection for motors](#)
- 17 [10,634,710](#)  [Ground network monitoring system](#)
- 18 [10,625,870](#)  [Secured lines for ballistic recovery system](#)
- 19 [10,608,505](#)  [Cooling motor controller with a motor with duct](#)
- 20 [10,604,028](#)  [Desired departure temperature for a battery in a vehicle](#)
- 21 [10,593,920](#)  [Capacitance reduction in battery systems](#)
- 22 [10,586,639](#)  [Array of three pole magnets](#)
- 23 [10,583,912](#)  [Combined fan and motor](#)
- 24 [10,573,920](#)  [Battery assembly techniques](#)
- 25 [10,562,620](#)  [Tilt-wing aircraft](#)

[Top](#)

[View Cart](#)

[Home](#)

[Quick](#)

[Advanced](#)

[Pat Num](#)

[Help](#)