

USPTO PATENT FULL-TEXT AND IMAGE DATABASE[Home](#)[Quick](#)[Advanced](#)[Pat Num](#)[Help](#)[Bottom](#)[View Cart](#)*Searching US Patent Collection...***Results of Search in US Patent Collection db for:****AN/"SEQUA CORPORATION": 35 patents.***Hits 1 through 35 out of 35*[Jump To](#)[Refine Search](#)

AN/"SEQUA CORPORATION"

**PAT.
NO.****Title**

- 1 [7,694,910](#)  [Wire/fiber ring and method for manufacturing the same](#)
- 2 [7,377,465](#)  [Wire/fiber ring and method for manufacturing the same](#)
- 3 [7,287,719](#)  [Wire/fiber ring method for manufacturing the same](#)
- 4 [7,246,474](#)  [Metal shingle system](#)
- 5 [7,118,063](#)  [Wire/fiber ring and method for manufacturing the same](#)
- 6 [6,178,886](#)  [Replaceable inking arrangement in a can decorator](#)
- 7 [6,167,805](#)  [Mandrel carrier for high speed can decorators](#)
- 8 [5,937,748](#)  [Metal coil printing mechanism and metal coil press machines including registration control](#)
- 9 [5,799,574](#)  [Spindle disc for high speed can decorators](#)
- 10 [5,749,631](#)  [Dual can rotating transfer plate to conveyor belt](#)
- 11 [5,687,605](#)  [Wiping unit for ram of bodymaker](#)
- 12 [5,626,046](#)  [Lightweight ram for bodymaker](#)
- 13 [5,609,100](#)  [Face valve apparatus for continuous motion can decorator](#)
- 14 [5,572,927](#)  [Vertical track for mandrel assembly of continuous motion can decorators](#)
- 15 [5,566,567](#)  [Rotary cup infeed](#)
- 16 [5,492,000](#)  [Rotary valve controlled apparatus for stripping cans from bodymaking ram](#)
- 17 [5,455,764](#)  [Register control system, particularly for off-line web finishing](#)
- 18 [5,361,960](#)  [Off-line web finishing system with splice and missing mark stability](#)
- 19 [5,337,659](#)  [Apparatus and method utilizing continuous motion offset and direct printing techniques for decorating cylindrical containers](#)
- 20 [5,323,981](#)  [Splicer tape system](#)
- 21 [5,265,532](#)  [Apparatus and method for decorating cylindrical containers](#)
- 22 [5,262,840](#)  [Multispectral reflectometer](#)
- 23 [5,231,926](#)  [Apparatus and method for substantially reducing can spacing and speed to match chain pins](#)
- 24 [5,224,640](#)  [Off-line web finishing system](#)
- 25 [5,208,435](#)  [Lightweight ram for bodymaker](#)
- 26 [5,186,100](#)  [Interchangeable inker having enclosed transmission](#)
- 27 [5,183,145](#)  [Apparatus and method for automatically positioning valve means controlling the application of pressurized air to mandrels on a rotating carrier](#)

- 28 [5,129,568](#)  [Off-line web finishing system](#)
- 29 [5,111,742](#)  [Mandrel trip subassembly for continuous motion can decorators](#)
- 30 [5,001,950](#)  [Rotary die cutter](#)
- 31 [4,928,511](#)  [Rotary cup infeed](#)
- 32 [4,921,093](#)  [Infeed means for high speed continuous motion can decorator](#)
- 33 [4,867,435](#)  [Apparatus for stacking folded sheet material](#)
- 34 [4,795,416](#)  [Apparatus for C-folding paper with variable spacing](#)
- 35 [4,721,504](#)  [Apparatus and method for folding cut sheet paper](#)
-

