

# US PATENT & TRADEMARK OFFICE

## PATENT APPLICATION FULL TEXT AND IMAGE DATABASE



( 1 of 1 )

<b>United States Patent Application</b>	<b>20180159756</b>
<b>Kind Code</b>	<b>A1</b>
<b>MATTHEWS; Steven Gregory ; et al.</b>	<b>June 7, 2018</b>

### INTEGRATED PERSONAL SAFETY AND EQUIPMENT MONITORING SYSTEM

#### Abstract

A monitoring and messaging system for monitoring status of a plurality of assets. The system includes a data collection and normalization module configured to accept data originating from a plurality of sensors and to convert the data to normalized data for subsequent processing by the system. The system has an identification module configured to receive the normalized data and assign a subset of the normalized data generated by one or more specific sensors of the plurality of sensors to an asset selected from a plurality of assets. The system has an analysis module which includes a database of asset rules defining status states of the asset. The analysis module is programmed to receive and compare the subset of normalized data with a subset of asset rules to determine a status state of the asset. The system also has an action module which is configured to receive the status state of the asset, generate a message representing the status state of the asset and to transmit the message to a concerned party.

Inventors: **MATTHEWS; Steven Gregory; (Calgary, CA) ; McLELLAN; James Frederick; (Calgary, CA) ; FORGET; Robert Wyatt; (Calgary, CA) ; MCDADE; James Paul; (Calgary, CA)**

**Applicant:**      **Name**      **City**      **State**      **Country**      **Type**

*Aware360 Ltd.*      Calgary      CA

Assignee: **Aware360 Ltd.**  
**Calgary**  
**CA**

Family ID: **62243551**

Appl. No.: **15/829558**

Filed:      **December 1, 2017**

#### Related U.S. Patent Documents

<u>Application Number</u>	<u>Filing Date</u>	<u>Patent Number</u>
62430110	Dec 5, 2016	

<b>Current U.S. Class:</b>	<b>1/1</b>
<b>Current CPC Class:</b>	G06F 21/552 20130101; H04L 43/0817 20130101; H04L 67/02









the requested resources. Upon receipt of resource status information from the device drivers, components of the device driver interface generate schedules for granting access to the requested resources. Further, the device driver interface components control access to the resources in accordance with the generated schedules including issuing responses to the requesting applications and the device drivers of the requested resources.

[0019] U.S. Patent Publication No. 2003/0120826, incorporated herein by reference in its entirety, describes a system for enabling a wireless wide area network communication capable of aggregating and disseminating information for the telematics domain, without the need of additional external network infrastructure, such as communication towers and central switch. The invention offers a new method for telematics, wherein each network object communicates only with network objects in its immediate surrounding using WLAN/PAN technologies. The information reaches remote network objects by continues exchanges of information between close network objects using WLAN/PAN technology. The system includes an aggregating disseminating communication component (ADCC) that is added to each network object. The ADCC collects traffic related information and builds an internal traffic map of the area. The underlying network object can initiate transmission of information using the ADCC. The ADCC is capable of receiving information and, if needed, the received information is updated via the underlying network object. The information is then exchanged to the next network object.

[0020] U.S. Patent Publication No. 2012/0010906, incorporated herein by reference in its entirety, describes a method for providing a customer with a competitive insurance quote from an insurance carrier includes collecting driving information relating to a customer for a time period, generating a driving report for the time period, providing the driving report to at least two potential insurance carriers, requesting insurance bids from the potential insurance carriers, and sending at least one of the insurance bids to the customer.

[0021] U.S. Patent Publication No. 2005/0182534, incorporated herein by reference in its entirety, describes a method of acquiring vehicle data from a vehicle data bus is disclosed. The method is responsive to the execution of a telematics application on a local telematics unit. The method comprises first accessing a local vehicle library, in response to vehicle data requests from the application. The local vehicle library then carries out steps comprising: retrieving vehicle data bus information from a database; using the vehicle data bus information to extract vehicle data from the vehicle data bus, the vehicle data corresponding to the requests for vehicle parameter data; interpreting the retrieved vehicle data; and providing the interpreted data to the telematics application to satisfy the request for vehicle data.

[0022] U.S. Patent Publication No. 2008/0319665, incorporated herein by reference in its entirety, describes methods, systems, and apparatuses for aftermarket telematics. In one aspect, there is provided an apparatus comprising a telematics control unit configured for consumer installation, consumer use, and the like. The apparatus can be installed in a vehicle. In another aspect, provided are systems and methods for operation of the apparatus.

[0023] U.S. Patent Publication No. 2013/0183924, incorporated herein by reference in its entirety, describes a system which establishes a perimeter around an area, and mobile devices within the established perimeter communicate with a server that provides and collects personal and asset safety information. The provided information might enable users associated with the mobile devices to plan actions or take routes based on a given criteria, such as a safest route, through display on the mobile device. The collected information from the mobile device might be location, emergency event, environmental factors, sensor information and the like, which might then be communicated to users and/or administrators of the system. Location information, such as a global positioning system (GPS), might provide tracking of mobile devices and users or assets associated with each mobile device. GPS functionality associates latitude, longitude and elevation (X-Y-Z coordinate axis) data with the collected and provided information.

[0024] U.S. Patent Publication No. 2011/0111728, incorporated herein by reference in its entirety, describes a system and method for providing a conduit to send information to emergency services from a wireless device. Also described are systems and methods for registering an alarm button on a wireless device and sending to public and/or private emergency services providers information related to the wireless device including its location, information about a wireless device end user and/or subscriber associated with the wireless device, and information recorded by one or more wireless devices during and subsequent to the time the alarm button is activated.



[0036] In certain embodiments, the concerned party is any one of or a combination of a rescue response team, a repair or maintenance team and a medical response team.

[0037] In certain embodiments, the concerned party is an individual associated with the asset and the message is routed back through the system and translated in the data collection and normalization module to data readable by a device associated with the asset.

[0038] In certain embodiments, the action module stores a copy of the transmitted message in a message database.

[0039] In certain embodiments, the asset has a plurality of assigned sensors, and wherein normal status of the asset as indicated by the assigned sensors represents a digital twin of the asset.

[0040] In certain embodiments, the data originating from the plurality of sensors are transmitted to the data collection and normalization module by a communication mode selected from the group consisting of direct internet connection, WiFi, Bluetooth, cellular network, radiofrequency transmission and satellite communication, or any combination thereof.

[0041] In certain embodiments, the system further comprises one or more ingress modules for receiving the data originating from the plurality of sensors and verifying that the received data has originated from sensors authorized by the system.

[0042] In certain embodiments, the message is transmitted to the concerned party by email, SMS, or push messaging.

[0043] In certain embodiments, the action control module includes action rules dictating whether or not action is required in response to a change in the status state of the asset.

## BRIEF DESCRIPTION OF THE DRAWINGS

[0044] Various objects, features and advantages of the invention will be apparent from the following description of particular embodiments of the invention, as illustrated in the accompanying drawings. Emphasis is placed upon illustrating the principles of various embodiments of the invention.

[0045] FIG. 1 is a block flow diagram of one embodiment of a system for monitoring individuals and equipment.

[0046] FIG. 2A is a block flow diagram of a first section of a second embodiment of a system for monitoring individuals and equipment.

[0047] FIG. 2B is a block flow diagram of a second section of the second embodiment of a system for monitoring individuals and equipment.

## DETAILED DESCRIPTION

### Rationale

[0048] Most devices are not connected to a software platform which is designed to provide a scalable, exception-based, digital communication pipeline between the device user and a monitoring center. This is because most devices and software outcomes are typically designed for the user and are not easily adapted for monitoring at a monitoring center. Since a typical software user interface is designed for the user and not the monitoring center, it does not allow an integrated user interface at the monitor level, meaning the center must continually monitor different software to see all the different devices. This causes inefficiencies and errors.

[0049] Current software for monitoring status of individuals is typically provided as a vertically locked outcome. These providers are not designed to connect many types of devices and to normalize the input received from these devices to allow standardized presentation of information to the monitor or response









active map display provides a means for geofencing for creation of alerts. For example, if an asset passes into or out of a geo-fenced area: a multi-asset notification is issued for all assets within a geo-fenced area by raising an SOS on the remote device user within the geo-fence. Customer-based or response center custom maps are configured for integration with the response center UI/UX.

## Process Flow within System Embodiments

[0090] Various aspects of the invention will now be described with reference to the figures. A number of possible alternative features are introduced during the course of this description. It is to be understood that, according to the knowledge and judgment of persons skilled in the art, such alternative features may be substituted in various combinations to arrive at different embodiments of the present invention.

### Embodiment 1

[0091] With reference to FIG. 1, there is shown a block diagram of one embodiment of the invention. Flow of data occurs in more than one direction as shown by a number of lateral, upward and double-headed arrows. For the sake of preserving clarity, the flow of data will be initially described with respect to the downward-pointing arrows throughout the entire diagram. Five sensors 2, 4, 6, 8 and 10 are shown in this example (however, it is to be understood that any number of sensors may be used to generate data for processing by the system). The different geometric shapes assigned to the sensors and devices of the sensing level are provided to indicate that these components differ from each other and are provided for the purpose of generating and transmitting data representing states of different parameters. Although indicated as "sensors" these components are either single stand-alone sensors, or are integrated within a single multi-sensor device such as a smartphone or safety pendant for example (not shown in FIG. 1). The sensors are configured to send a stream of data to the data normalization and message translation module 20. Depending upon availability of network communication modes, the transmission may occur through a direct internet connection, WiFi, Bluetooth, cellular network, radio transmission (via a protocol such as ZigBee, for example) or satellite communication. Methods and systems for selecting communication modes based on availability and cost are described in US Patent Application No. 2015/0282061, which is commonly owned and incorporated herein by reference in its entirety).

[0092] Data packets generated by the sensors 2, 4, 6, 8 and 10 are converted to a normalized format for subsequent processing by the system. The data normalization and message translation module 20 thus includes a processor programmed with all the data conversion algorithms required to handle all formats of data generated by the sensors 2, 4, 6, 8 and 10. Module 20 is provided to address the fact that various manufacturers of sensors and devices will use different formats for packaging and transmitting data. This module 20 converts or normalizes the data to permit continued processing in the system.

[0093] The normalized data is transferred to the identification module 30, where information regarding the sensor from which it was generated is associated with an asset. As defined herein, an "asset" is one or more individuals, one or more units of equipment including vehicles, one or more buildings or structures, one or more defined locations, or any combination thereof). All operations relating to assignment of sensors or devices to an asset are performed in the identification module 30. Such operations include rule sets for association of sensors/devices with assets. Such rule sets are provided to prevent inappropriate association with of certain sensors with certain assets. For example, an oil pressure sensor should not be associated with an individual and a personal safety pendant should not be associated with a generator.

[0094] After processing by the identification module 30, the data is transmitted to the analysis module 40. The analysis module 40 includes a database 41 containing asset rules which define status states for each asset contained therein. The analysis module 40 is programmed to compare packets of the normalized data with specified asset rules to determine a status state of the asset. The status state is transmitted to the action module 50.

[0095] The action module 50, receives the status state of the asset and subjects the status state to a set of action rules dictating whether or not action is required (such as requesting a maintenance call or a rescue from a third party, for example). Additionally the action rules will dictate whether or not a confirmatory message should be sent back to the device or sensor which generated the data which resulted in a change in the status state of the asset.









and therefore a sensor-based indication that the main furnace is malfunctioning represents a major event requiring immediate attention. The analysis module of the system would include a rule indicating that a furnace malfunction is a high level alert to be addressed immediately by dispatching an HVAC specialist to the work site via the event generation functionality.

[0114] On the other hand, an indication of low oil pressure from a sensor associated with one of the five generators at the worksite could be considered an event considered not to be particularly dangerous. The analysis level of the system would include a rule indicating that the oil pressure alert is a low-level maintenance alert to be addressed within 24 hours by personnel residing at the work camp to attend to routine maintenance of the generator.

### Example 3: Monitoring of a Work Group Asset Including Workers and Equipment

[0115] Another situation applicable to embodiments of the system described herein is to collectively monitor a combination of individuals and equipment, including vehicles collectively represent an asset operating under conditions of extremely cold temperatures, representing hazardous conditions for the workers. Thus, a set of rules is developed to define conditions which would require alerts and/or actions to address problems at the worksite. The workers each carry a safety pendant device with sensors providing data indicating the worker's safety status and units of equipment each have sensors for providing data regarding proper functioning of the equipment. One possible arrangement relates to systems and methods described in U.S. patent application Ser. No. 15/172,818 which is commonly owned and incorporated herein by reference in its entirety. This document describes systems and methods for monitoring a convoy of vehicles traveling on an ice road. Temperature sensors inside the vehicles to register sudden drops in temperature, vehicle sensors to determine speed and GPS receivers to provide location data. An accident involving a vehicle results in transmission of data through the system and produces a series of data-based insights that would stipulate rule-based event generation to require immediate rescue of the driver of the vehicle and deployment of additional assets to attempt to recover the vehicle from the accident site. This could include notification to the trailing driver of the convoy (which is part of the workgroup and also part of the asset) to stop his or her vehicle and approach the accident scene on foot to assess the accident and/or lend rescue assistance. The rules could further stipulate that a check-in is required by the trailing driver within a specified period of time.

### EQUIVALENTS AND SCOPE

[0116] As will be appreciated by one skilled in the art, aspects of the present disclosure may be illustrated and described herein in any of a number of patentable classes or context including any new and useful process, machine, manufacture, or composition of matter, or any new and useful improvement thereof. Accordingly, aspects of the present disclosure may be implemented entirely hardware, entirely software (including firmware, resident software, micro-code, etc.) or combining software and hardware implementation that may all generally be referred to herein as a "module," "component," or "system." Furthermore, aspects of the present disclosure may take the form of a computer program product embodied in one or more computer readable media having computer readable program code embodied thereon.

[0117] Any combination of one or more computer readable media may be utilized. The computer readable media may be a computer readable signal medium or a computer readable storage medium. A computer readable storage medium may be, for example, but not limited to, an electronic, magnetic, optical, electromagnetic, or semiconductor system, apparatus, or device, or any suitable combination of the foregoing. More specific examples (a non-exhaustive list) of the computer readable storage medium would include the following: a portable computer diskette, a hard disk, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), an appropriate optical fiber with a repeater, a portable compact disc read-only memory (CD-ROM), an optical storage device, a magnetic storage device, or any suitable combination of the foregoing. In the context of this document, a computer readable storage medium may be any tangible medium that can contain, or store a program for use by or in connection with an instruction execution system, apparatus, or device.

[0118] A computer readable signal medium may include a propagated data signal with computer readable program code embodied therein, for example, in baseband or as part of a carrier wave. Such a propagated signal may take any of a variety of forms, including, but not limited to, electro-magnetic, optical, or any suitable combination thereof. A computer readable signal medium may be any computer readable medium

that is not a computer readable storage medium and that can communicate, propagate, or transport a program for use by or in connection with an instruction execution system, apparatus, or device. Program code embodied on a computer readable signal medium may be transmitted using any appropriate medium, including but not limited to wireless, wireline, optical fiber cable, radio frequency, or any suitable combination of the foregoing.

[0119] Computer program code for carrying out operations for aspects of the present disclosure may be written in any combination of one or more programming languages, including an object-oriented programming language, conventional procedural programming languages, and dynamic programming languages or other programming languages. Data transmission may be effected through any type of network, including a local area network (LAN) or a wide area network (WAN), or a connection may be made to an external computer (for example, through the internet using an internet service provider) or in a cloud computing environment.

[0120] Aspects of the present disclosure are described herein with reference to flowchart illustrations and/or block diagrams of methods, apparatuses (systems) and computer program products according to embodiments of the disclosure. It will be understood that each block of the flowchart illustrations and/or block diagrams, and combinations of blocks in the flowchart illustrations and/or block diagrams, can be implemented by computer program instructions. These computer program instructions may be provided to a processor of a general purpose computer, special purpose computer, or other programmable data processing apparatus to produce a machine, such that the instructions, which execute via the processor of the computer or other programmable instruction execution apparatus, create a mechanism for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks. Such computer program instructions may also be stored in a computer readable medium that when executed can direct a computer, other programmable data processing apparatus, or other devices to function in a particular manner, such that the instructions when stored in the computer readable medium produce an article of manufacture including instructions which when executed, cause a computer to implement the function/act specified in the flowchart and/or block diagram block or blocks. The computer program instructions may also be loaded onto a computer, other programmable instruction execution apparatus, or other devices to cause a series of operational steps to be performed on the computer, other programmable apparatuses or other devices to produce a computer implemented process such that the instructions which execute on the computer or other programmable apparatus provide processes for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks.

[0121] Any patent, publication, internet site, or other disclosure material, in whole or in part, that is said to be incorporated by reference herein is incorporated herein only to the extent that the incorporated material does not conflict with existing definitions, statements, or other disclosure material set forth in this disclosure. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

[0122] Unless otherwise defined, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs.

[0123] While this invention has been particularly shown and described with references to embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the scope of the invention encompassed by the appended claims.

\* \* \* \* \*

