

[USPTO PATENT FULL-TEXT AND IMAGE DATABASE](#)[Home](#)[Quick](#)[Advanced](#)[Pat Num](#)[Help](#)[Next List](#)[Bottom](#)[View Cart](#)

Searching US Patent Collection...

**Results of Search in US Patent Collection db for:****AN/"EAGLE HARBOR TECHNOLOGIES, INC": 51 patents.****Hits 1 through 50 out of 51**










Final 1 Hits

Jump To

Refine Search

AN/"EAGLE HARBOR TECHNOLOGIES, INC"

<b>PAT. NO.</b>	<b>Title</b>
1 <a href="#">11,303,269</a>	<a href="#">High voltage pre-pulsing</a>
2 <a href="#">11,302,518</a>	<a href="#">Efficient energy recovery in a nanosecond pulser circuit</a>
3 <a href="#">11,250,988</a>	<a href="#">High voltage transformer</a>
4 <a href="#">11,227,745</a>	<a href="#">Plasma sheath control for RF plasma reactors</a>
5 <a href="#">11,222,767</a>	<a href="#">Nanosecond pulser bias compensation</a>
6 <a href="#">11,171,568</a>	<a href="#">Transformer resonant converter</a>
7 <a href="#">11,159,156</a>	<a href="#">High voltage nanosecond pulser</a>
8 <a href="#">11,137,372</a>	<a href="#">Eddy current nondestructive evaluation device with rotating permanent magnets and pickup coils</a>
9 <a href="#">11,108,384</a>	<a href="#">Nonlinear transmission line high voltage pulse sharpening with energy recovery</a>
10 <a href="#">11,101,108</a>	<a href="#">Nanosecond pulser ADC system</a>
11 <a href="#">11,095,280</a>	<a href="#">Efficient IGBT switching</a>
12 <a href="#">11,075,058</a>	<a href="#">Spatially variable wafer bias power system</a>
13 <a href="#">11,004,660</a>	<a href="#">Variable output impedance RF generator</a>
14 <a href="#">10,991,553</a>	<a href="#">Nanosecond pulser thermal management</a>
15 <a href="#">10,985,740</a>	<a href="#">High voltage nanosecond pulser with variable pulse width and pulse repetition frequency</a>
16 <a href="#">10,978,955</a>	<a href="#">Nanosecond pulser bias compensation</a>
17 <a href="#">10,903,047</a>	<a href="#">Precise plasma control system</a>
18 <a href="#">10,896,809</a>	<a href="#">High voltage switch with isolated power</a>
19 <a href="#">10,892,141</a>	<a href="#">Nanosecond pulser pulse generation</a>
20 <a href="#">10,892,140</a>	<a href="#">Nanosecond pulser bias compensation</a>
21 <a href="#">10,847,346</a>	<a href="#">High voltage resistive output stage circuit</a>
22 <a href="#">10,811,230</a>	<a href="#">Spatially variable wafer bias power system</a>
23 <a href="#">10,804,886</a>	<a href="#">High voltage pre-pulsing</a>
24 <a href="#">10,796,887</a>	<a href="#">Efficient nanosecond pulser with source and sink capability for plasma control applications</a>
25 <a href="#">10,790,816</a>	<a href="#">Solid-state replacement for tube-based modulators</a>

- 26 [10,777,388](#)  [Arbitrary waveform generation using digital pulses](#)
  - 27 [10,734,906](#)  [Nanosecond pulser](#)
  - 28 [10,707,864](#)  [High voltage nanosecond pulser](#)
  - 29 [10,666,198](#)  [Efficient high power microwave generation using recirculating pulses](#)
  - 30 [10,659,019](#)  [Nanosecond pulser ADC system](#)
  - 31 [10,607,814](#)  [High voltage switch with isolated power](#)
  - 32 [10,483,089](#)  [High voltage resistive output stage circuit](#)
  - 33 [10,460,911](#)  [High voltage resistive output stage circuit](#)
  - 34 [10,460,910](#)  [High voltage resistive output stage circuit](#)
  - 35 [10,389,345](#)  [Efficient IGBT switching](#)
  - 36 [10,382,022](#)  [High voltage nanosecond pulser with variable pulse width and pulse repetition frequency](#)
  - 37 [10,373,755](#)  [High voltage transformer](#)
  - 38 [10,320,373](#)  [RF production using nonlinear semiconductor junction capacitance](#)
  - 39 [10,304,661](#)  [Arbitrary waveform generation using nanosecond pulses](#)
  - 40 [10,282,567](#)  [High voltage inductive adder](#)
  - 41 [10,268,846](#)  [High voltage inductive adder](#)
  - 42 [10,224,822](#)  [Nanosecond pulser](#)
  - 43 [10,027,314](#)  [Nonlinear transmission line high voltage pulse sharpening](#)
  - 44 [10,020,800](#)  [High voltage nanosecond pulser with variable pulse width and pulse repetition frequency](#)
  - 45 [9,960,763](#)  [High voltage nanosecond pulser](#)
  - 46 [9,929,004](#)  [High frequency, repetitive, compact toroid-generation for radiation production](#)
  - 47 [9,706,630](#)  [Galvanically isolated output variable pulse generator disclosure](#)
  - 48 [9,655,221](#)  [High frequency, repetitive, compact toroid-generation for radiation production](#)
  - 49 [9,601,283](#)  [Efficient IGBT switching](#)
  - 50 [9,495,563](#)  [Analog integrator system and method](#)
- 

